



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

THHN750BK500 THHN 750 STR Black 500'

Southwire Company

| | |
|------------------|--|
| Catalog Number | THHN750BK500 |
| Manufacturer | Southwire Company |
| Description | 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also Rated MTW. Simpull Technology For Easier Pulling. |
| Weight per unit | 2.5 (lbs/ft) |
| Product Category | THHN-T90-STR (Stranded) |

Features

| | |
|----------------------|---------------|
| Conductor Size | 750 |
| media | Yes |
| Number of Conductors | 1 |
| Tip Size | 500 ft. Spool |
| Voltage Rating | 600 |

Material, Color, and Finish

| | |
|---------------------|-------|
| Insulation Material | PVC |
| Jacket Material | Nylon |

Dimensions and Weight

| | |
|--------|-----|
| Length | 500 |
|--------|-----|

Descriptions

| | |
|------------------------|--|
| Description | THHN 750 STR BLACK 500' |
| extra long description | SWC 32099401 THHN 750 Str Cu SIM Bk |
| Long Description | 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN and THWN-2. Also rated MTW. SIMpull Technology for Easier Pulling. |
| Product Type | THHN 750 STR Cu Sim BK 500R |
| Special Features | No Lube |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Copper |
| GTIN | 00032886234507 |
| Manufacturers Part Number | 32099401 |
| UPC | 032886234507 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---------------|
| Category Description | BUILDING WIRE |
| Type | THHN-2 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|-------|
| Carton | 500 |
| Weight Per foot | 2.464 |

Uses, Certifications, and Standards

| | |
|-------------|------------|
| Application | Commerical |
|-------------|------------|