

**FLUKE**®

## Fluke TL224 SureGrip™ Insulated Test Leads



### **Overview:**

Test leads are an integral part of the complete measurement system and extend the capabilities of your digital multimeter. The TL224 SureGrip™ Insulated Test leads offer reinforced strain relief and includes banana jack termination for a variety of test lead configurations. SureGrip™ accessories are designed to improve steadiness in slippery hands. Rubber over molded surfaces and finger-hugging curves give the user a comfortable, reliable grip on the accessory so they can focus on making an accurate measurement.

### **Features:**

- DMM test leads (red, black) with safety shrouded, standard diameter banana plugs
- Right angle connector on one end and straight connector on the other
- Reinforced strain relief
- 1.5 meter silicone-insulated wire resists heat & cold
- CAT IV 600 V, CAT III 1000 V, 10 A rating. UL listed
- One year warranty

Model Name

Description

---

**Fluke TL224**

Fluke TL224 SureGrip™ Insulated Test Leads

---

**FLUKE**®

## Fluke TL224 SureGrip™ Insulated Test Leads



### **Overview:**

Test leads are an integral part of the complete measurement system and extend the capabilities of your digital multimeter. The TL224 SureGrip™ Insulated Test leads offer reinforced strain relief and includes banana jack termination for a variety of test lead configurations. SureGrip™ accessories are designed to improve steadiness in slippery hands. Rubber over molded surfaces and finger-hugging curves give the user a comfortable, reliable grip on the accessory so they can focus on making an accurate measurement.

### **Features:**

- DMM test leads (red, black) with safety shrouded, standard diameter banana plugs
- Right angle connector on one end and straight connector on the other
- Reinforced strain relief
- 1.5 meter silicone-insulated wire resists heat & cold
- CAT IV 600 V, CAT III 1000 V, 10 A rating. UL listed
- One year warranty

Model Name

Description

---

**Fluke TL224**

Fluke TL224 SureGrip™ Insulated Test Leads

---