

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Size

TR70R 250V RK5 TD Fuse Mersen Fuses

Catalog Number	TR70R
Manufacturer	Mersen Fuses
Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 70A Blade Tri-Onic®
Weight per unit	0.3500 (lbs/each)
Product Category	Current Limiting
Features	
AC Voltage Rating	250
amperage rating	70
class	Class RK5
connection	Blade
interrupt rating	200
Voltage Rating	250
Material, Color, and Finish Body Material	PolyTube
Dimensions and Weight	

5.88 x 0.06



Descriptions

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Description	250V RK5 TD FUSE
extra long description	Mersen TR70R Fuse TR-R - Class RK5
Features	Tri-Onic TR-R current-limiting time-delay fuses are engineered for overcurrent protection of motors, transformers, service entrance equipment, feeders and branch-circuits. The time-delay characteristics of the TR-R safely handle harmless starting currents and inrush currents associated with today's motors and transformers.
Long Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 70A Blade Tri-Onic®
Product Type	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 70A Blade
Short Description	250V 70A 5 7/8x1 1/16 RK5
Special Features	Time-delay Current-limiting AC & DC rated Optional solid state SmartSpot blown fuse indicator Time-delay for motor start-ups and transformer inrush currents without nuisance opening Current-limiting for low peak let-thru current Rejection-style design prevents replacement errors (when used with recommended fuse blocks) Easy-to-read label for quick brand recognition and replacement Metal-embossed date and catalog number for traceability and lasting identification Fiberglass body provides dimensional stabili
nufacturer Information	

Brand	Mersen
GTIN	00782001747978
Manufacturers Part Number	TR70R
UPC	782001747978

Taxonomies, Classifications, and Categories

Packaging		
Carton	1	
Weight Per each	0.35	

CLASS RK5

Uses, Certifications, and Standards

Type

Application	Motor circuits Mains Feeders Branch circuits Transformers
	Service entrance equipment General-purpose equipment
Mounting	Clip
standard	UL listed to standard 248-12 File E2137 CSA certified to standard
	C22.2 no. 248.12 DC listed to UL standard 248 TRS only