

# Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



## General specifications

Product Name	Catalog Number
Eaton TR timing relay	TRL07
UPC	Product Length/Depth
786685313580	2.56 in
Product Height	Product Width
3.43 in	0.69 in
Product Weight	Warranty
0.16 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
TUV	cULus Listed
CE Marked	CSA Certified

defaultTaxonomyAttributeLabel

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

SPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

Input voltage

24-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Catalogs

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions

Installation instructions

TRL04 and TRL07 Installation Instructions

Specifications and datasheets

Eaton Specification Sheet - TRL07

# Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



## General specifications

Product Name	Catalog Number
Eaton TR timing relay	TRL07
UPC	Product Length/Depth
786685313580	2.56 in
Product Height	Product Width
3.43 in	0.69 in
Product Weight	Warranty
0.16 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
TUV	cULus Listed
CE Marked	CSA Certified

defaultTaxonomyAttributeLabel

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

SPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

Input voltage

24-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Catalogs

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions

Installation instructions

TRL04 and TRL07 Installation Instructions

Specifications and datasheets

Eaton Specification Sheet - TRL07