

Specifications



Eaton TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

General specifications

| | |
|-----------------------------|--|
| PRODUCT NAME | Eaton TR timing relay |
| CATALOG NUMBER | TRL07 |
| UPC | 786685313580 |
| PRODUCT LENGTH/DEPTH | 2.56 in |
| PRODUCT HEIGHT | 3.43 in |
| PRODUCT WIDTH | 0.69 in |
| PRODUCT WEIGHT | 0.16 lb |
| WARRANTY | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| COMPLIANCES | TUV CE Marked |
| CERTIFICATIONS | cULus Listed CSA Certified |



Powering Business Worldwide

Product specifications

| | |
|------------------------------|---|
| FREQUENCY RATING | 50-60 Hz |
| ENCLOSURE | IP40 |
| ENCLOSURE MATERIAL | Self-extinguishing plastic |
| CONTACT CONFIGURATION | SPDT |
| TIME DELAY | 0.05 seconds-100 hours |
| SERIES | TR |
| FUNCTIONS | Single shot leading or trailing edge voltage controlled and control input ON delay control signal start ON/OFF delay Trailing edge OFF Power triggered Flasher-pause first |
| INPUT VOLTAGE | 24-240 Vac/dc |
| MOUNTING METHOD | Compact DIN rail |

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - TR107](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

