



# Commercial grade receptacles


## Commercial grade straight blade receptacles

### Product description


2-pole, 3-wire grounding  
 15A, 125V/AC  
 20A, 125V/AC  
 NEMA 5-15R, 5-20R



TRBR15



TR1877



WRBR15

### Tamper resistant commercial grade receptacles



| Rating                       | A                      | V/AC        | NEMA  | Description                | Color suffix | Catalog no. |  |
|------------------------------|------------------------|-------------|---|----------------------------|--------------|-------------|--|
| 15                           | 125                    | 5-15R       | Duplex receptacle, back & side wire           | A, B, BK, GY, LA, V, W     | □ TRBR15__   | • •         |  |
|                              |                        |             | Single receptacle, side wire                  | A, B, BK, LA, V, W         | □ TR817__*   | • •         |  |
|                              |                        |             | Decorator duplex receptacle, back & side wire | LA, V, W                   | □ TR6252__   | • •         |  |
|                              |                        |             | Decorator single receptacle, back & side wire | B, BK, V, W                | □ TR6250__   | • •         |  |
|                              |                        |             | Duplex receptacle, side wire                  | A, B, BK, GY, LA, V, W     | □ TRCR15__*  |             |  |
| 20                           | 125                    | 5-20R       | Duplex receptacle, back & side wire           | A, B, BK, GY, LA, RD, V, W | □ TRBR20__   | • •         |  |
|                              |                        |             | Single receptacle, side wire                  | A, B, BK, LA, V, W         | □ TR1877__*  | • •         |  |
|                              |                        |             | Decorator duplex receptacle, back & side wire | A, B, BK, GY, LA, V, W     | □ TR6352__   | • •         |  |
|                              |                        |             | Decorator single receptacle, side wire        | LA, V, W                   | □ TR6350__*  | • •         |  |
| Duplex receptacle, side wire | A, B, BK, GY, LA, V, W | □ TRCR20__* |   |                            |              |             |  |

\* Not Fed Spec

### Weather resistant commercial grade receptacles



| Rating | A   | V/AC  | NEMA                                | Description | Color suffix | Catalog no. |  |
|--------|-----|-------|-------------------------------------|-------------|--------------|-------------|--|
| 15     | 125 | 5-15R | Duplex receptacle, back & side wire | B, V, W     | □ WRBR15__   | • •         |  |
| 20     | 125 | 5-20R | Duplex receptacle, back & side wire | B, V, W     | □ WRBR20__   | • •         |  |

### Tamper & weather resistant commercial grade receptacles



| Rating | A   | V/AC  | NEMA                                | Description | Color suffix | Catalog no. |  |
|--------|-----|-------|-------------------------------------|-------------|--------------|-------------|--|
| 15     | 125 | 5-15R | Duplex receptacle, back & side wire | B, GY, V, W | □ TWRBR15__  | • •         |  |
| 20     | 125 | 5-20R | Duplex receptacle, back & side wire | B, V, W     | □ TWRBR20__  | • •         |  |

### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)



**Specification information:** Tamper resistant commercial receptacles: A-32, Weather resistant commercial receptacles: A-32, Tamper & weather resistant commercial receptacles: A-32

**Compliances, specifications and availability are subject to change without notice.**

➤ ArrowLink option available. Add "M" suffix to standard catalog number (example AH8300W, AH8300WM). For ordering information on ArrowLink & ArrowLink SPD connectors, see Page A-5

Build-to-spec customizable devices - Page A-6

RoHS compliant - Page Q-32



TR Tamper resistant WWR Weather resistant TWR Tamper & weather resistant

# Commercial grade receptacles


## Commercial grade straight blade receptacles

### Product description


2-pole, 3-wire grounding  
 15A, 125V/AC  
 20A, 125V/AC  
 NEMA 5-15R, 5-20R



TRBR15



TR1877



WRBR15

### Tamper resistant commercial grade receptacles



| Rating | A   | V/AC  | NEMA  | Description                | Color suffix | Catalog no. |  |
|--------|-----|-------|---|----------------------------|--------------|-------------|--|
| 15     | 125 | 5-15R | Duplex receptacle, back & side wire           | A, B, BK, GY, LA, V, W     | □ TRBR15__   | • •         |  |
|        |     |       | Single receptacle, side wire                  | A, B, BK, LA, V, W         | □ TR817__*   | • •         |  |
|        |     |       | Decorator duplex receptacle, back & side wire | LA, V, W                   | □ TR6252__   | • •         |  |
|        |     |       | Decorator single receptacle, back & side wire | B, BK, V, W                | □ TR6250__   | • •         |  |
|        |     |       | Duplex receptacle, side wire                  | A, B, BK, GY, LA, V, W     | □ TRCR15__*  |             |  |
| 20     | 125 | 5-20R | Duplex receptacle, back & side wire           | A, B, BK, GY, LA, RD, V, W | □ TRBR20__   | • •         |  |
|        |     |       | Single receptacle, side wire                  | A, B, BK, LA, V, W         | □ TR1877__*  | • •         |  |
|        |     |       | Decorator duplex receptacle, back & side wire | A, B, BK, GY, LA, V, W     | □ TR6352__   | • •         |  |
|        |     |       | Decorator single receptacle, side wire        | LA, V, W                   | □ TR6350__*  | • •         |  |
|        |     |       | Duplex receptacle, side wire                  | A, B, BK, GY, LA, V, W     | □ TRCR20__*  |             |  |

\* Not Fed Spec

### Weather resistant commercial grade receptacles



| Rating | A   | V/AC  | NEMA                                | Description | Color suffix | Catalog no. |  |
|--------|-----|-------|-------------------------------------|-------------|--------------|-------------|--|
| 15     | 125 | 5-15R | Duplex receptacle, back & side wire | B, V, W     | □ WRBR15__   | • •         |  |
| 20     | 125 | 5-20R | Duplex receptacle, back & side wire | B, V, W     | □ WRBR20__   | • •         |  |

### Tamper & weather resistant commercial grade receptacles



| Rating | A   | V/AC  | NEMA                                | Description | Color suffix | Catalog no. |  |
|--------|-----|-------|-------------------------------------|-------------|--------------|-------------|--|
| 15     | 125 | 5-15R | Duplex receptacle, back & side wire | B, GY, V, W | □ TWRBR15__  | • •         |  |
| 20     | 125 | 5-20R | Duplex receptacle, back & side wire | B, V, W     | □ TWRBR20__  | • •         |  |

### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)



**Specification information:** Tamper resistant commercial receptacles: A-32, Weather resistant commercial receptacles: A-32, Tamper & weather resistant commercial receptacles: A-32

**Compliances, specifications and availability are subject to change without notice.**

➤ ArrowLink option available. Add "M" suffix to standard catalog number (example AH8300W, AH8300WM). For ordering information on ArrowLink & ArrowLink SPD connectors, see Page A-5

Build-to-spec customizable devices - Page A-6

RoHS compliant - Page Q-32

TR Tamper resistant WWR Weather resistant TWR Tamper & weather resistant