

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Category Description

Туре

TY25M 7.31" Ty-Rap (Bulk) Abb Installation Products, Inc

Catalog Number	TY25M
Manufacturer	Abb Installation Products, Inc
Description	High Performance Cable Tie For Indoor Applications, Natural Color Nylon 6.6, Length Of 186MM (7.3 Inches) For Bundle Diameter Up to 48MM (1.89 Inches), Width Of 4.83MM (0.19 Inches), Tensile Strength Rating Of 222 Newtons (50 Pounds), Operating Temperature Of -60 Degrees Celsius (-76 F) to 85 Degrees Celsius (185 F), Bulk Pack
Weight per unit	0.0020 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
Tensile Strength	50;222
Dimensions and Weight	
Length	7.2
Thickness	0.05
Width	0.19
Descriptions	
Description	7.31" TY-RAP (BULK)
extra long description	ABB TY25M CABLE TIE 50LB 7.31IN NAT
Long Description	High Performance Cable Tie for Indoor applications, Natural Color Nylon 6.6, Length of 186mm (7.3 Inches) for Bundle Diameter up to 48mm (1.89 Inches), Width of 4.83mm (0.19 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Operating Temperature of -60 Degrees Celsius (-76 F) to 85 Degrees Celsius (185 F), Bulk Pack
Product Type	Cable Tie 50LB 7.31IN Natural Nylon
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time
Manufacturer Information	
Brand	Ty-Rap
GTIN	00786210824574
Manufacturers Part Number	TY25M
UPC	786210824574

HIGH PERFORMANCE

Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability	
minimum qty	1000
Packaging	
Carton	1000
Weight Per each	0.002
Uses, Certifications, and Standards	
standard	UL F49405, CSA 2884