

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## TY28MX 14.19" Outdoor Ty-Rap Abb Installation Products, Inc

Catalog Number	TY28MX
Manufacturer	Abb Installation Products, Inc
Description	High Performance Cable Tie, Weather and Ultraviolet Resistant For Indoor and Outdoor Applications, Black Color Nylon 6.6, Length Of 361MM (14.2 Inches) For Bundle Diameter Up to 102MM (4.02 Inches), Width Of 4.83MM (0.19 Inches), Tensile Strength Rating Of 222.4 Newtons (50 Pounds), Operating Temperature Of -60 Degrees Celsius (-76 F) to 105 Degrees Celsius (221 F), Bulk Pack
Weight per unit	0.0100 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
Tensile Strength	50
<b>Dimensions and Weight</b>	
Length	14.2
Thickness	0.05
Width	0.19
Descriptions	
	14.19" OUTDOOR TY-RAP
extra long description	ABB TY28MX CABLE TIE 50LB 14.2IN UV
Long Description	High Performance Cable Tie, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Black Color Nylon 6.6, Length of 361mm (14.2 Inches) for Bundle Diameter up to 102mm (4.02 Inches), Width of 4.83mm (0.19 Inches), Tensile Strength Rating of 222.4 Newtons (50 Pounds), Operating Temperature of -60 Degrees Celsius (-76 F) to 105 Degrees Celsius (221 F), Bulk Pack
Product Type	Cable Tie 50LB 14.2IN Uv Black Nylo
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time
Manufacturer Information	
Brand	·
GTIN	00786210824840
Manufacturers Part Number	TY28MX
UPC	786210824840



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	HIGH PERFORMANCE
Availability minimum qty	1000
Packaging	
Carton	1000
Package	5000
Weight Per each	0.01
Uses, Certifications, and Standards	
standard	UL E49405