

Type

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## TY524MX 5.50" Uv Rated "Ty-Rap" Cable Tie Abb Installation Products, Inc

ADD INSTAIIATION PLOUUC		
Catalog Number	TY524MX	
Manufacturer	Abb Installation Products, Inc	
Description	Cable Tie, Black Polyamide (Nylon 6.6) For Temperatures Up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant Fo Indoor and Outdoor Applications, Length Of 137MM (5.4 Inches) Width Of 3.6MM (0.14 Inches), Thickness Of 1MM (0.04 Inch), Tensile Strength Rating Of 178 Newtons (40 Pounds)	
Weight per unit	0.0029 (lbs/each)	
Product Category	Cable Ties & Wraps	
Features		
Tensile Strength	40:178	
<b>Dimensions and Weight</b>		
Length	5.4	
Thickness	0.04	
Width	0.14	
Descriptions		
Description	5.50" UV RATED "TY-RAP" CABLE TIE	
extra long description	ABB TY524MX CBL TIE 30LB 5.5 UV BLA	
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 137mm (5.4 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 178 Newtons (40 Pounds)	
Product Type	CBL Tie 30LB 5.5 Uv Black 2-PC Dis	
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time	
Manufacturer Information		
Brand	Ty-Rap	
GTIN		
Manufacturers Part Number	TY524MX	
UPC	786210806990	
Taxonomies, Classifications, and (	<u> </u>	
category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps	

HIGH PERFORMANCE



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Packaging**

Carton	100	
Package	1000	
Weight Per each	0.0029	