



16100 South Lathrop Ave  
Harvey, IL 60426

OFFICE / 708-339-1610  
TOLL-FREE / 800-882-5543  
WEB / [atkore.com](http://atkore.com)

September 5, 2018

## **AFC LIQUID-TUFF™ FLEXIBLE CONDUIT SAFETY DATA SHEET (SDS) & CALIFORNIA PROP 65**

To Whom It May Concern:

Safety Data Sheets (SDS) are not provided for the attached list of products because these products are considered to be an "article" under the OSHA Hazard Communication Standard (HSC), 29 CFR 1910.1200.

This standard has an exemption for articles. To be considered as an article, the product has to be a manufactured item meeting the following criteria:

- During manufacture, the article must be formed to a specific shape or design
- The end-use functions are dependent in whole or in part on its shape or design and
- The product does not release or result in exposure to a hazardous chemical under normal conditions of use.

Products covered by this letter are not considered to be or to contain hazardous chemicals based on evaluations made by our company under the OSHA Hazard Communication Standard, 29 CFR 1910.1200. However, if your intent is to further process the product, please contact us so we can address that issue.

For more information, please refer to the following website:

<https://www.osha.gov/Publications/OSHA3514.html>

Atkore has also reviewed its compliance obligations under California's updated Proposition 65 Clear & Reasonable Warning Regulations and has concluded that foreseeable use of the attached list of products do not result in exposures of listed chemicals requiring a warning.

Very truly yours,

*Ruth Ensing*

Ruth Ensing  
Certification Specialist  
Atkore International  
Phone: 708-915-1543  
Email: [rensing@atkore.com](mailto:rensing@atkore.com)

| <i>PRODUCT FAMILY</i> | <i>DESCRIPTION</i>                                                             | <i>PRODUCT SERIES</i> |
|-----------------------|--------------------------------------------------------------------------------|-----------------------|
| LFMC                  | Non UL Oil Resistant/High Temperature                                          | 5900                  |
| LFMC                  | Non UL Very Flexible                                                           | 6100                  |
| Type LFMC             | 3/8, 1/2, 3/4, 1 1/2, 2, 2 1/2, 3, 3 1/2, 4 Liquid-Tuff Flexible Metal Conduit | 6200                  |
| LFMC                  | CSA Hydrotite Com-Blue                                                         | 6300                  |
| Type LFMC             | 1/2, 3/4, 1 1/2, 2, 2 1/2, 3 UL & CSA Computer Blue                            | 6400                  |
| Type LFMC             | 3/8, 1/2, 3/4, 1 1/2, 2 UL & CSA Low Smoke Zero Halogen                        | 6700                  |
| LFMC                  | 3/8, 1/2, 3/4, 1 1/2, 2 Non UL Low Smoke Zero Halogen                          | 6750                  |
| LFMC                  | Non UL Extreme Temperature                                                     | 6800                  |
| Type LFMC             | 3/8, 1/2, 3/4, 2, 2 1/2, 3, 3 1/2, 4 UL Hi-Low Temperature                     | 6900                  |
| LFMC                  | 3/8, 1/2, 1 1/2, 2 UL & CSA NSF® 169 Component for Splash Zones                | SZ00                  |
| LFMC                  | 3/8, 1/2, 3/4, 1 1/2, 2, 2 1/2, 3, 4 CSA Hydrotite                             | HC00                  |