



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## UNY605SA 2" Male Union *Crouse-Hinds*

Catalog Number	UNY605SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Uny Union, Rigid/Imc, Male, Copper-Free Aluminum, 2"
Weight per unit	1.4 (lbs/each)
Product Category	Aluminum

### Features

connection	Threaded
dimensions	4.0900 IN X 3.8800 IN X 3.8800 IN

### Descriptions

Description	2" MALE UNION
extra long description	CRS-H UNY605 SA 2 NPT MALE UNY AL U
Features	Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion unions are also available, which allow for expansion and contraction of conduit and compensate for conduit cut too short. Available in a variety of materials, including stainless steel, to suit customer preferences. Explosionproof elbows allow for a 90° change in direction to the conduit run, or when terminating at a box or fit
Long Description	Eaton Crouse-Hinds series UNY union, Rigid/IMC, Male, Copper-free aluminum, 2"
Product Type	2 NPT Male Uny Al Union
Special Features	3-13/16 In Diameter X 3-3/4 In Length

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274101996
Manufacturers Part Number	UNY605 SA
UPC	782274101996

### Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Union

### Packaging

Carton	1
Package	2
Weight Per each	1.42



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2