



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



USE10STBK500 Cu Use #10 STR Black 500' *Southwire Company*

Catalog Number	USE10STBK500
Manufacturer	Southwire Company
Description	Service Entrance Cable, Conductors Shall Be Annealed Copper, Cross-Linked Polyethylene (XLP) Insulated, As Manufactured By Southwire Company or Approved Equal Additional Information, Underground Service Entrance Application, Black, Copper Conductor Material, 320 A (60°C);380 A (75°C);430 A (90°C) Current Rating, Cross-Linked Polyethylene Insulation Material, 95 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 983 Mil Outside Diameter, 1000 FT Overall Length, Reel P
Weight per unit	0.0490 (lbs/ft)
Product Category	Use RHH-RHW-STR (Stranded)

Features

Conductor Size	10
Number of Conductors	1

Dimensions and Weight

Length	500
--------	-----

Descriptions

Description	CU USE #10 STR BLACK 500'
extra long description	SWC 11344903 USE 10 Str Cu Bk 500Sp

Manufacturer Information

Brand	Copper
GTIN	00032886276019
Manufacturers Part Number	11344903
UPC	032886276019

Taxonomies, Classifications, and Categories

Category Description	BUILDING WIRE
Type	USE-2

Packaging

Carton	500
Weight Per foot	0.049