Eaton V48M28T7516CU

Catalog Number: V48M28T7516CU

Eaton General purpose ventilated transformer, Fungus proof, CU windings, DOE 2016, NEMA 2, FR942, 220°C, 75 kVA, Floor/wall mnt upright only, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 75 kVA

General specifications



transformer

Catalog Number V48M28T7516CU

Eaton General purpose ventilated

UPC

01 0

Product Length/Depth

786680192012 Product Height

24 in

43 in

Product Width

Product Weight

30.5 in

632 lb

Warranty

Compliances

Eaton Selling Policy 25-000, one (1) year DOE2016 Efficient

from the date of installation of the

Product or eighteen (18) months from the Certifications

date of shipment of the Product,

UL Listed

whichever occurs first.

OL LISIEU

Catalog Notes

10 CFR Part 431 (2016) Efficient



Photo is representative



Physical Attributes

Coil material

Copper

Enclosure

NEMA 2

Frame

FR942

Insulation

220 °C

Material

Copper windings

Mounting

Floor or wall, upright only

Tap size

2 at +2.5%, 4 at -2.5%

Type

Energy-efficient ventilated dry-type transformer

Wiring connection

280B

Performance Ratings

Efficiency

10 CFR Part 431-2016 (DOE 2016)

Frequency rating

60 Hz

Kva Rating

75 kVA

Primary voltage

480 V delta

Secondary Voltage

208Y/120 V

Sound Level

NEMA ST-20

Temperature rise

150 °C rise

Volt ampere rating

75 kVA

Voltage rating

480 Vac-208Y/120 Vac

Resources

Brochures

Eaton's high-efficiency dry-type transformers

Eaton's low-voltage dry-type distribution transformers

Specifications and datasheets

Eaton Specification Sheet - V48M28T7516CU

Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia

Eaton V48M28T7516CU

Catalog Number: V48M28T7516CU

Eaton General purpose ventilated transformer, Fungus proof, CU windings, DOE 2016, NEMA 2, FR942, 220°C, 75 kVA, Floor/wall mnt upright only, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 75 kVA

General specifications



transformer

Catalog Number V48M28T7516CU

Eaton General purpose ventilated

UPC

01 0

Product Length/Depth

786680192012 Product Height

24 in

43 in

Product Width

Product Weight

30.5 in

632 lb

Warranty

Compliances

Eaton Selling Policy 25-000, one (1) year DOE2016 Efficient

from the date of installation of the

Product or eighteen (18) months from the Certifications

date of shipment of the Product,

UL Listed

whichever occurs first.

OL LISIEU

Catalog Notes

10 CFR Part 431 (2016) Efficient



Photo is representative



Physical Attributes

Coil material

Copper

Enclosure

NEMA 2

Frame

FR942

Insulation

220 °C

Material

Copper windings

Mounting

Floor or wall, upright only

Tap size

2 at +2.5%, 4 at -2.5%

Type

Energy-efficient ventilated dry-type transformer

Wiring connection

280B

Performance Ratings

Efficiency

10 CFR Part 431-2016 (DOE 2016)

Frequency rating

60 Hz

Kva Rating

75 kVA

Primary voltage

480 V delta

Secondary Voltage

208Y/120 V

Sound Level

NEMA ST-20

Temperature rise

150 °C rise

Volt ampere rating

75 kVA

Voltage rating

480 Vac-208Y/120 Vac

Resources

Brochures

Eaton's high-efficiency dry-type transformers

Eaton's low-voltage dry-type distribution transformers

Specifications and datasheets

Eaton Specification Sheet - V48M28T7516CU

Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia