



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



WR1010 1/0 to 1/0 H Tap

Abb Installation Products, Inc

Catalog Number	WR1010
Manufacturer	Abb Installation Products, Inc
Description	Aluminum Wide Range H-Type Compression Connector Main: 1/0-4 Acsr, 2/0-4 STR., 1- 2 Sol., Tap: 1/0-4 Acsr, 2/0-4 STR., 1-2 Sol., Die: 0
Weight per unit	0.0850 (lbs/each)
Product Category	Pole Line & Distribution Hardw

Features

connection	Compression
insulation	None
Material	Aluminum
Number of Conductors	2
Wire Size	Main: 1/0 to #4 ACSR or 2/0 to #4 STR or #1 to #2 SOL AWG , Tap: 1/0 to #4 ACSR or 2/0 to #4 STR or #1 to #2 SOL AWG

Material, Color, and Finish

Housing Material	Aluminum
------------------	----------

Dimensions and Weight

Size	Length 1-3/4 inch
------	-------------------

Descriptions

Description	1/0 TO 1/0 H TAP
extra long description	ABB WR1010 AL HTYPE COMP CONN 1/0-4
Long Description	Aluminum Wide Range H-Type Compression Connector Main: 1/0-4 ACSR, 2/0-4 Str., 1- 2 Sol., Tap: 1/0-4 ACSR, 2/0-4 Str., 1-2 Sol., Die: 0
Product Type	Al Htype Comp Conn 1/0-4ASCR 2/0-4
Special Features	Made of 1350 Aluminum Alloy for high strength and high conductivity. Standard Compression tools and dies install all sizes - no special tools needed. Field-proven ribbed design enables excellent connector/conductor contact without distorting the conductor's shape. Fold-in tabs provide tab interlock as tool closes. Prefilled with oxide inhibitor held captive in the rib/connection area

Manufacturer Information

Brand	Blackburn Mechanical
GTIN	00783786107452
Manufacturers Part Number	WR1010
UPC	783786107452



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description T&B C TAP LUGS

Type H-Type Compression Tap Connector

Packaging

Carton 25

Package 250

Weight Per each 0.085

Uses, Certifications, and Standards

Application For Combinations of Aluminum to Aluminum and Aluminum to Copper Conductors

environmental conditions All Seasons / Conditions

Mounting None

standard RUS Accepted. Complies with ANSI C119.4 Specifications

Temperature Rating up to 90 C