

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

700 York Ave. 67401-0000, KS Salina Phone: 785-914-5431 Fax: 785-914-5432



UPC

WR1010 1/0 to 1/0 H Tap *Abb Installation Products, Inc*

Catalog Number	WR1010	
Manufacturer	Abb Installation Products, Inc	
Description	Aluminum Wide Range H-Type Compression Connector Main:	
	1/0-4 Acsr, 2/0-4 STR., 1- 2 Sol., Tap: 1/0-4 Acsr, 2/0-4 STR., 1-2	
	Sol., Die: 0	
Weight per unit	0.0850 (lbs/each)	
Product Category	Pole Line & Distribution Hardw	
Features		
connection	Compression	
insulation	None	
Number of Conductors	2	
Wire Size	Main: 1/0 to #4 ACSR or 2/0 to #4 STR or #1 to #2 SOL AWG, Tap: 1/0 to #4 ACSR or 2/0 to #4 STR or #1 to #2 SOL AWG	
Material, Color, and Finish		
Housing Material	Aluminum	
Dimensions and Weight		
Size	Length 1-3/4 inch	
Descriptions		
Description	1/0 TO 1/0 H TAP	
extra long description	ABB WR1010 AL HTYPE COMP CONN 1/0-4	
Long Description	Aluminum Wide Range H-Type Compression Connector Main: 1/0-4 ACSR, 2/0-4 Str., 1- 2 Sol., Tap: 1/0-4 ACSR, 2/0-4 Str., 1-2 Sol., Die: 0	
Product Type	Al Htype Comp Conn 1/0-4ASCR 2/0-4	
Special Features	Made of 1350 Aluminum Alloy for high strength and high conductivity. Standard Compression tools and dies install all sizes - no special tools needed. Field-proven ribbed design enables excellent connector/conductor contact without distorting the conductor's shape. Fold-in tabs provide tab interlock as tool closes. Prefilled with oxide inhibitor held captive in the rib/connection area	
Manufacturer Information Brand	Blackburn Mechanical	
GTIN	00783786107452	
Manufacturers Part Number	WR1010	
Managara and a tradition		

783786107452



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

250

0.085

700 York Ave. 67401-0000, KS Salina Phone: 785-914-5431 Fax: 785-914-5432

Taxonomies, Cl	lassifications,	and	Categories
----------------	-----------------	-----	------------

Category Description	T&B C TAP LUGS
Туре	H-Type Compression Tap Connector
Packaging	
Carton	25

Uses, Certifications, and Standards

Package Weight Per each

of continuations, and otaliaal	45
Application	For Combinations of Aluminum to Aluminum and Aluminum to
	Copper Conductors
environmental conditions	All Seasons / Conditions
Mounting	None
standard	RUS Accepted. Complies with ANSI C119.4 Specifications