

# ELLIOTT ELECTRIC SUPPLY 7520 Eastgate Blvd Suite 100 37122-0000, TN Mt. Juliet Phone: 615-257-4146 507-415 257-4147

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 615-257-4147



### WS2000l Occ/Vac Sensor, Pir, 120/277V, Iv Hubbell Wiring Devices

Catalog Number	WS2000I
Manufacturer	Hubbell Wiring Devices
Description	Lighting Controls, Occupancy/Vacancy Sensors, Wall Switch,
	Passive Infrared Technology, 120/277V Ac, Ivory
Weight per unit	0.2060 (lbs/each)
Product Category	Lighting Occupancy Sensors

#### **Features**

connector	Screwed Terminal
load	Lighting Circuit
pallet quantity	1350
supply voltage	120/277 AC
Voltage Rating	120/277

#### **Dimensions and Weight**

Size	4	1	5	in	X	1	.82	in	X	1.6	52	in
UILU			$\sim$	• • • • •	' '\		. 02		٠			

#### **Descriptions**

Description	OCC/VAC SENSOR,PIR,120/277V,IV
extra long description	HWDK WS2000I OCC/VAC SENSOR,PIR,120
Features	Standard Passive Infrared Technology requires a clear,
	unobstructed line of sight for detection, because it senses
	occupancy as movement of heat emitted from the body against
	the background space. A segmented Fresnel lens divides a
	coverage area into zones. Movement across zones is interpreted
	as occupancy. Excellent for small room control.
Long Description	Lighting Controls, Occupancy/Vacancy Sensors, Wall Switch,
	Passive Infrared Technology, 120/277V AC, Ivory
Product Type	Occ/Vac Sensor, Pir, 120/277V, Iv
Special Features	Standard Product

#### **Manufacturer Information**

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585256306
Manufacturers Part Number	WS2000I
series	Passive Infrared
UPC	783585256306

#### **Taxonomies, Classifications, and Categories**

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Type	Manual/Auto



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7520 Eastgate Blvd Suite 100 37122-0000, TN Mt. Juliet Phone: 615-257-4146 Fax: 615-257-4147

_		•
1100	/ A A	INA
	K AII	
Pac	Nuu	ши

Carton	1	
Package	10	
Weight Per each	0.206	

#### Uses, Certifications, and Standards

Application	Compatible with most LED and CFL
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Mounting Screws
standard	cULus Listed To UL773A