



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



WSXAL Almond WL SW Sensor

Lithonia Lighting - Acuity

Catalog Number	WSXAL
Manufacturer	Lithonia Lighting - Acuity
Description	Fixture Mount Interchangeable Lens Sensor , High Bay 360 Lens & High Bay Bi-Directional Aisleway Lens , 347-480 Vac
Weight per unit	0.3100 (lbs/each)
Product Category	Lighting Occupancy Sensors

Features

average life	Not Applicable
dimmable	Yes
Hardware	Yes
Lamp Included	Not Applicable
Material	Plastic
Power Source	Hardwired
Shape	Rectangular
supply voltage	120, 277
Voltage Rating	120,277
Warranty	5

Material, Color, and Finish

Finish	Gloss
Lens Material	Plastic

Dimensions and Weight

Height	4.5
Length	1.5
Width	2.25

Descriptions

Description	ALMOND WL SW SENSOR
extra long description	LITH WSX AL Wall Switch Sensor, Lig
Long Description	Fixture Mount Interchangeable Lens Sensor , High Bay 360 Lens & High Bay Bi-Directional Aisleway Lens , 347-480 VAC
Product Type	Sensor
Special Features	The WSX Family of wall switch occupancy sensors provides simple and cost effective solutions for commercial and residential lighting control applications. All WSX Family sensors have a stylish low profile appearance, soft-click buttons, and provide small motion detection up to 20 ft (6.10 m), making them perfect for private offices, private rest rooms, closets, copy rooms, or any other small enclosed space. Additionally, all WSX Family sensors have a patent-pending wiring method that enables them to functi



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	SENSOR SWITCH
GTIN	00820476167782
Manufacturers Part Number	WSX AL
UPC	820476167782

Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Type	SENSOR

Packaging

Carton	1
Weight Per each	0.31

Uses, Certifications, and Standards

Application	Education,Government,Healthcare,Hospitality,House of Worship,Manufacturing,Offices & Banks,Retail,Sports and Recreation,Warehouses
environmental conditions	Indoor
Mounting	Semi-recessed
standard	cUL,UL