

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



WSXGY Gray WL SW Sensor Lithonia Lighting

Catalog Number	WSXGY
Manufacturer	Lithonia Lighting
Description	Wall Switch Sensor , Gray, Sku - 219R09
Weight per unit	
Product Category	Lighting Occupancy Sensors

Features

141 03	
average life	87,600
dimmable	Yes
Hardware	Yes
Material	Plastic
Maximum Operating Temperature	60
media	Yes
Power Source	Hardwired
sensing range	180 degrees
Shape	Rectangular
supply voltage	120, 277
Voltage Rating	120,277
Warranty	5

Material, Color, and Finish

Color	Gray	
Finish	Gloss	
Lens Material	Plastic	

Dimensions and Weight

Height	4.5
Length	1.5
Width	2.25



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

11	nc	cri	n	tı	$\boldsymbol{\wedge}$	nc
.,		L-I I	L,		w	113

Description	GRAY WL SW SENSOR
extra long description	LITH WSX GY Wall Switch Sensor, Gra
Long Description	Wall Switch Sensor , Gray, SKU - 219R09
Product Type	Sensor
Special Features	The WSX Family of wall switch occupancy sensors provides simple and cost effective solutions for commercial and residential lighting control applications. All WSX Family sensors have a stylish low profile appearance, soft-click buttons, and provide small motion detection up to 20 ft (6.10 m), making them perfect for private offices, private rest rooms, closets, copy rooms, or any other small enclosed space. Additionally, all WSX Family sensors have a patent-pending wiring method that enables them to functi
Manufacturer Information	
Brand	Lithonia Lighting
GTIN	00820476167799
Manufacturers Part Number	WSX GY
UPC	820476167799

Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Туре	Wallstation

Packaging

onagg	
Carton	1
Weight Per each	0.31

Uses, Certifications, and Standards

Application	Education, Government, Healthcare, Hospitality, House of
	Worship, Manufacturing, Offices & Banks, Retail, Sports and
	Recreation, Warehouses
environmental conditions	Indoor
Mounting	Semi-recessed
standard	cUL,UL