


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





X75M 3/4" X FM5 Conduit Rody

Catalog Number	X75M
Manufacturer	Charles Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 5 Conduit Outlet Body Malleable Iron, X Shape, 3/4"
Weight per unit Product Category	
Features	
connection	Threaded / Set Screw
dimensions	6.0800 IN X 1.9700 IN X 2.9300 IN
Form	Form F
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	1.97
Hub Size	
Length	
Width	2.93
Descriptions	
Description	3/4" X FM5 CONDUIT BODY
extra long description	
Features	Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They ar also available with a h
Long Description	Eaton Crouse-Hinds series Condulet Form 5 conduit outlet body, Malleable iron, X shape, 3/4"
Product Type	3/4 Form 5 X Fitting

Manufacturer Information

Brand	Eaton
GTIN	00784564003010
Manufacturers Part Number	X75M
UPC	784564003010



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, a	nd Categories
Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	1
Package	10
Weight Per each	1.47
Uses, Certifications, and Stand	lards
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
Enclosure	Condulet

UL 514B, CSA C22.2, CUL