

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

XHHW40RDPCS	AI XHHW 4/0 STR Red	PCS
Kina Wire Inc		

King Wire Inc.	
Catalog Number	XHHW40RDPCS
Manufacturer	King Wire Inc.
Description	Aluminum Building Wire, Abrasion, Moisture, Heat and Sunlight Resistant Insulation;Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Red, Aluminum Conductor Material, 4/0 Awg Conductor Size, 205 A Current Rating, Polyethylene Insulation Material, 55 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 19 - Strands, 0.590 In Outside Diameter, 1000 FT Overall Length, Carton Package Type, Directive 2002/95/Ec;Federal Specificat
Weight per unit	0.2440 (lbs/ft)
Product Category	XHHW-STR (Stranded)
Descriptions	
Description	AL XHHW 4/0 STR RED PCS
Manufacturer Information	
Brand	Aluminum
Taxonomies, Classifications, and (Categories
Category Description	ALUM BUILDING WIRE
Packaging	1
Carton	0.244
Weight Per foot	0.244