

# Eaton XTOE005BCS

Catalog Number: XTOE005BCS

Eaton C440 electronic overload relay, XT IEC Electronic Overload Relay, 1-5A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton C440 electronic overload relay	XTOE005BCS
<b>UPC</b>	<b>Product Length/Depth</b>
786685416403	1.77 in
<b>Product Height</b>	<b>Product Width</b>
4.33 in	1.42 in
<b>Product Weight</b>	<b>Compliances</b>
0.87 lb	CE Marked
	RoHS Compliant
	ATEX Compliant

## Certifications

EN 60947  
UL Listed  
CSA Certified  
IEC 60947

## defaultTaxonomyAttributeLabel

### Overload range

1-5A

### Type

Electronic overload relay

### Frame size

45 mm

### Mounting method

Direct

### Contact configuration

NO, NC

### Trip type

Selectable 10 A, class 10 ,20, 30

## Resources

### Brochures

[C440 Electronic Overload Relay](#)

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[XTOE\\_B 2D PDF](#)

[XTOE\\_B AutoCAD 2D Footprint](#)

[XTOE\\_B 2D Drawing Xchange](#)

[XTOE\\_B 3D Model Xchange](#)

[XTOE\\_B 3D Inventor](#)

[XTOE\\_B AutoCAD 2D Footprint \(mm\)](#)

### Installation instructions

[XTOE/ZEB IEC Electronic Overload - Self Powered](#)

### Specifications and datasheets

[Eaton Specification Sheet - XTOE005BCS](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)