

# Eaton XTOE020CCS

Catalog Number: XTOE020CCS

Eaton C440 electronic overload relay, XT IEC, 4-20A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type

## General specifications

Product Name	Catalog Number
Eaton C440 electronic overload relay	XTOE020CCS
UPC	Product Length/Depth
786685416472	1.8 in
Product Height	Product Width
4.3 in	1.42 in
Product Weight	Compliances
0.87 lb	ATEX Compliant
	RoHS Compliant
	CE Marked

## Certifications

IEC 60947  
CSA Certified  
EN 60947  
UL Listed



## defaultTaxonomyAttributeLabel

### Overload range

4-20A

### Type

Electronic overload relay

### Frame size

45 mm

### Mounting method

Direct

### Contact configuration

NO, NC

### Trip type

Selectable 10 A, class 10 ,20, 30

## Resources

### Brochures

C440 Electronic Overload Relay

### Catalogs

Eaton's Volume 5—Motor Control and Protection

### Drawings

XTOE\_C 3D Model Xchange

XTOE\_C 2D PDF

XTOE\_C 2D Drawing Xchange

XTOE\_C 3D Inventor

XTOE\_C AutoCAD 2D Footprint

XTOE\_C AutoCAD 2D Footprint (mm)

### Installation instructions

XTOE/ZEB IEC Electronic Overload - Self Powered

### Specifications and datasheets

Eaton Specification Sheet - XTOE020CCS



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia

# Eaton XTOE020CCS

Catalog Number: XTOE020CCS

Eaton C440 electronic overload relay, XT IEC, 4-20A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton C440 electronic overload relay	XTOE020CCS
<b>UPC</b>	<b>Product Length/Depth</b>
786685416472	1.8 in
<b>Product Height</b>	<b>Product Width</b>
4.3 in	1.42 in
<b>Product Weight</b>	<b>Compliances</b>
0.87 lb	ATEX Compliant
	RoHS Compliant
	CE Marked

## Certifications

IEC 60947  
CSA Certified  
EN 60947  
UL Listed



## defaultTaxonomyAttributeLabel

### Overload range

4-20A

### Type

Electronic overload relay

### Frame size

45 mm

### Mounting method

Direct

### Contact configuration

NO, NC

### Trip type

Selectable 10 A, class 10 ,20, 30

## Resources

### Brochures

C440 Electronic Overload Relay

### Catalogs

Eaton's Volume 5—Motor Control and Protection

### Drawings

XTOE\_C 3D Model Xchange

XTOE\_C 2D PDF

XTOE\_C 2D Drawing Xchange

XTOE\_C 3D Inventor

XTOE\_C AutoCAD 2D Footprint

XTOE\_C AutoCAD 2D Footprint (mm)

### Installation instructions

XTOE/ZEB IEC Electronic Overload - Self Powered

### Specifications and datasheets

Eaton Specification Sheet - XTOE020CCS



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia