Specifications





Eaton C440 electronic overload relay, XT IEC Electronic Overload Relay, 20-100A overload range, 105 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type

General specifications

PRODUCT NAME	Eaton C440 electronic overload relay
CATALOG NUMBER	XTOE100GCS
UPC	786685416571
PRODUCT LENGTH/DEPTH	7.5 in
PRODUCT HEIGHT	6.5 in
PRODUCT WIDTH	3.253 in
PRODUCT WEIGHT	0.87 lb
COMPLIANCES	CE Marked RoHS Compliant ATEX Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947







Product specifications

OVERLOAD RANGE	20-100A
ТҮРЕ	Electronic overload relay
FRAME SIZE	105 mm
MOUNTING METHOD	Direct
CONTACT CONFIGURATION	NO, NC
TRIP TYPE	Selectable 10 A, class 10 ,20, 30

Resources	
BROCHURES	<u>C440 Electronic Overload</u> <u>Relay</u>
CATALOGS	<u>Motor Control and</u> <u>Protection, NEMA</u> <u>Contactors and Starters,</u> <u>Volume 5, Tab 2</u>
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOE100GCS

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

