

# Specifications

Photo is representative

## Eaton XTOE1P6BCS

Eaton C440 electronic overload relay, XT IEC Electronic Overload Relay, 0.33-1.65A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type



### General specifications

<b>PRODUCT NAME</b>	Eaton C440 electronic overload relay
<b>CATALOG NUMBER</b>	XTOE1P6BCS
<b>UPC</b>	786685416397
<b>PRODUCT LENGTH/DEPTH</b>	1.77 in
<b>PRODUCT HEIGHT</b>	4.33 in
<b>PRODUCT WIDTH</b>	1.42 in
<b>PRODUCT WEIGHT</b>	0.87 lb
<b>COMPLIANCES</b>	CE Marked RoHS Compliant ATEX Compliant
<b>CERTIFICATIONS</b>	EN 60947 UL Listed CSA Certified IEC 60947

### Product specifications

<b>OVERLOAD RANGE</b>	0.33-1.65A
<b>TYPE</b>	Electronic overload relay
<b>FRAME SIZE</b>	45 mm
<b>MOUNTING METHOD</b>	Direct
<b>CONTACT CONFIGURATION</b>	NO, NC
<b>TRIP TYPE</b>	Selectable 10 A, class 10 ,20, 30

### Resources

<b>BROCHURES</b>	<a href="#">C440 Electronic Overload Relay</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - XTOE1P6BCS</a>

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

