

# Eaton XTCEXFAG11

Catalog Number: XTCEXFAG11

Contactor Accessory - Auxiliary Contact, Two-pole, Screw terminals, D-G Frame size, 1NO-1NC contact configuration, 16A conventional thermal rating, Front mounting, used with XTRE control relays

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton motor control auxiliary contact	XTCEXFAG11
<b>UPC</b>	<b>Product Length/Depth</b>
782116354702	1.5 in
<b>Product Height</b>	<b>Product Width</b>
2 in	1 in
<b>Product Weight</b>	<b>Warranty</b>
0.07 lb	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
ATEX Compliant	IEC 60947
CCC Marked	EN 60947
CE Marked	UL Listed
	CSA Certified

## Catalog Notes

Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.

## defaultTaxonomyAttributeLabel

### Number Of Poles

Two-pole

### Type

Contactory Accessory - Auxiliary Contact

### Used with

XTRE control relays

### Frame size

D-G

### Terminals

Screw

### Contact configuration

1 NO-1 NC

### Mounting method

Front

### Conventional thermal current

16A

### Quantity

5

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Specifications and datasheets

[Global Data Sheet - XTCEXFAG11](#)

[Eaton Specification Sheet - XTCEXFAG11](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)

# Eaton XTCEXFAG11

Catalog Number: XTCEXFAG11

Contactor Accessory - Auxiliary Contact, Two-pole, Screw terminals, D-G Frame size, 1NO-1NC contact configuration, 16A conventional thermal rating, Front mounting, used with XTRE control relays



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton motor control auxiliary contact	XTCEXFAG11
<b>UPC</b>	<b>Product Length/Depth</b>
782116354702	1.5 in
<b>Product Height</b>	<b>Product Width</b>
2 in	1 in
<b>Product Weight</b>	<b>Warranty</b>
0.07 lb	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
ATEX Compliant	IEC 60947
CCC Marked	EN 60947
CE Marked	UL Listed
	CSA Certified

## Catalog Notes

Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.

## defaultTaxonomyAttributeLabel

### Number Of Poles

Two-pole

### Type

Contactory Accessory - Auxiliary Contact

### Used with

XTRE control relays

### Frame size

D-G

### Terminals

Screw

### Contact configuration

1 NO-1 NC

### Mounting method

Front

### Conventional thermal current

16A

### Quantity

5

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Specifications and datasheets

[Global Data Sheet - XTCEXFAG11](#)

[Eaton Specification Sheet - XTCEXFAG11](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)