


Additional Accessories

Mechanical Interlock ①			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXMLB	XTCE007B–XTCE015B, XTCF020B	5	XTCEXMLB
			
XTCEXML_	XTCE018C–XTCE032C, XTCF032C–XTCF045C	1	XTCEXMLC
			
	XTCE040D–XTCE072D, XTCF063D–XTCF080D	1	XTCEXMLD
	XTCE080F–XTCE170G, XTCF125G–XTCF200G	1	XTCEXMLG ③
			
XTCEXMLM	XTCE185H–XTCE570M	1	XTCEXMLM
			
XTCEXMLN	XTCE580N–XTCEC10N	1	XTCEXMLN ③
			

Reversing Link Kits

For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXRLB	XTCE007B–XTCE015B	1	XTCEXRLB ④
			
XTCEXRL_	XTCE018C–XTCE032C	1	XTCEXRLC
			
	XTCE040D–XTCE065D	1	XTCEXRLD
	XTCE080F–XTCE150G	1	XTCEXRLG
			

Main current wiring for reversing combinations. Includes paralleling bridge and reversing bridge. Does not include mechanical interlock, see table on this page.

Star-Delta (Wye-Delta) Link Kits			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXSDLB	XTCE007B–XTCE015B	1	XTCEXSDLB ③
			
XTCEXSDL_	XTCE018C–XTCE032C	1	XTCEXSDLC
			
	XTCE040D–XTCE072D	1	XTCEXSDLD
	XTCE080F–XTCE095F	1	XTCEXSDLF
	XTCE115G–XTCE150G	1	XTCEXSDLG

Main current wiring for star-delta (wye-delta) combinations. includes paralleling bridge, reversing bridge and star-delta bridge. Does not include mechanical interlock, see table on this page.

Paralleling Bridge			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXPBB	XTCE007B–XTCE015B	20	XTCEXPBB
			
XTCEXPBC	XTCE018C–XTCE032C	20	XTCEXPBC
			

Component part of reversing link kit (XTCEXRL_). Parallels the phases on the line-side of two contactors.

Reversing Bridge			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXRBB	XTCE007B–XTCE015B	20	XTCEXRBB
			
XTCEXR_B	XTCE018C–XTCE032C	20	XTCEXRBC
			
	XTCE040D–XTCE065D	10	XTCEXRBD

Component part of reversing link kit (XTCEXRL_). Reverses the phases on the load-side of two contactors.

Notes

- ① For two contactors with AC or DC operated magnet system which are horizontally or vertically mounted. For Frames B–G, mechanical lifespan is 2.5×10^6 operations and the distance between contactors is 0 mm. For Frames L–N, mechanical lifespan is 5×10^6 operations and no auxiliary contact can be mounted between the mechanical interlock and the contactor—the distance between contactors is 15 mm.
- ② Orders must be placed in multiples of package quantity listed.
- ③ XTCEXMLG and XTCEXMLN consist of an interlock element and mounting plate.
- ④ Also includes interlocking bridge (XTCEXLBB). The following control cables are integrated for electrical interlock: K1M: A1–K2M: 21; K1M: 21–K2M: A1; K1M: A2–K2M: A2.

Additional Accessories

Mechanical Interlock ①			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXMLB	XTCE007B–XTCE015B, XTCF020B	5	XTCEXMLB
			
XTCEXML_	XTCE018C–XTCE032C, XTCF032C–XTCF045C	1	XTCEXMLC
			
	XTCE040D–XTCE072D, XTCF063D–XTCF080D	1	XTCEXMLD
	XTCE080F–XTCE170G, XTCF125G–XTCF200G	1	XTCEXMLG ③
XTCEXMLM	XTCE185H–XTCE570M	1	XTCEXMLM
			
XTCEXMLN	XTCE580N–XTCEC10N	1	XTCEXMLN ③
			

Reversing Link Kits

For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXRLB	XTCE007B–XTCE015B	1	XTCEXRLB ④
			
XTCEXRL_	XTCE018C–XTCE032C	1	XTCEXRLC
			
	XTCE040D–XTCE065D	1	XTCEXRLD
	XTCE080F–XTCE150G	1	XTCEXRLG

Main current wiring for reversing combinations. Includes paralleling bridge and reversing bridge. Does not include mechanical interlock, see table on this page.

Star-Delta (Wye-Delta) Link Kits			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXSDLB	XTCE007B–XTCE015B	1	XTCEXSDLB ③
			
XTCEXSDL_	XTCE018C–XTCE032C	1	XTCEXSDLC
			
	XTCE040D–XTCE072D	1	XTCEXSDLD
	XTCE080F–XTCE095F	1	XTCEXSDLF
	XTCE115G–XTCE150G	1	XTCEXSDLG

Main current wiring for star-delta (wye-delta) combinations. includes paralleling bridge, reversing bridge and star-delta bridge. Does not include mechanical interlock, see table on this page.

Paralleling Bridge			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXPBB	XTCE007B–XTCE015B	20	XTCEXPBB
			
XTCEXPBC	XTCE018C–XTCE032C	20	XTCEXPBC
			

Component part of reversing link kit (XTCEXRL_). Parallels the phases on the line-side of two contactors.

Reversing Bridge			
For Use with...	Pkg. Qty. ②	Catalog Number	
XTCEXRBB	XTCE007B–XTCE015B	20	XTCEXRBB
			
XTCEXR_B	XTCE018C–XTCE032C	20	XTCEXRBC
			
	XTCE040D–XTCE065D	10	XTCEXRBD

Component part of reversing link kit (XTCEXRL_). Reverses the phases on the load-side of two contactors.

Notes

- ① For two contactors with AC or DC operated magnet system which are horizontally or vertically mounted. For Frames B–G, mechanical lifespan is 2.5×10^6 operations and the distance between contactors is 0 mm. For Frames L–N, mechanical lifespan is 5×10^6 operations and no auxiliary contact can be mounted between the mechanical interlock and the contactor—the distance between contactors is 15 mm.
- ② Orders must be placed in multiples of package quantity listed.
- ③ XTCEXMLG and XTCEXMLN consist of an interlock element and mounting plate.
- ④ Also includes interlocking bridge (XTCEXLBB). The following control cables are integrated for electrical interlock: K1M: A1–K2M: 21; K1M: 21–K2M: A1; K1M: A2–K2M: A2.