


## Additional Accessories

Mechanical Interlock <sup>①</sup>


|   | For Use with...                         | Pkg. Qty. <sup>②</sup> | Catalog Number               |
|---|---|------------------------|------------------------------|
|  | XTCE007B–XTCE015B,<br>XTCF020B          | 5                      | <b>XTCEXMLB</b>              |
|  | XTCE018C–XTCE032C,<br>XTCF032C–XTCF045C | 1                      | <b>XTCEXMLC</b>              |
|   | XTCE040D–XTCE072D,<br>XTCF063D–XTCF080D | 1                      | <b>XTCEXMLD</b>              |
|   | XTCE080F–XTCE170G,<br>XTCF125G–XTCF200G | 1                      | <b>XTCEXMLG</b> <sup>③</sup> |
|  | XTCE185H–XTCE570M                       | 1                      | <b>XTCEXMLM</b>              |
|  | XTCE580N–XTCEC10N                       | 1                      | <b>XTCEXMLN</b> <sup>③</sup> |

## Reversing Link Kits

|   | For Use with...   | Pkg. Qty. <sup>②</sup> | Catalog Number               |
|---|-------------------|------------------------|------------------------------|
|  | XTCE007B–XTCE015B | 1                      | <b>XTCEXRLB</b> <sup>④</sup> |
|  | XTCE018C–XTCE032C | 1                      | <b>XTCEXRLC</b>              |
|   | XTCE040D–XTCE065D | 1                      | <b>XTCEXRLD</b>              |
|   | XTCE080F–XTCE150G | 1                      | <b>XTCEXRLG</b>              |

Main current wiring for reversing combinations. Includes paralleling bridge and reversing bridge. Does not include mechanical interlock, see table on this page.

## Star-Delta (Wye-Delta) Link Kits

|   | For Use with...   | Pkg. Qty. <sup>②</sup> | Catalog Number                |
|---|-------------------|------------------------|-------------------------------|
|  | XTCE007B–XTCE015B | 1                      | <b>XTCEXSDLB</b> <sup>③</sup> |
|  | XTCE018C–XTCE032C | 1                      | <b>XTCEXSDLC</b>              |
|   | XTCE040D–XTCE072D | 1                      | <b>XTCEXSDLD</b>              |
|   | XTCE080F–XTCE095F | 1                      | <b>XTCEXSDLF</b>              |
|   | XTCE115G–XTCE150G | 1                      | <b>XTCEXSDLG</b>              |

Main current wiring for star-delta (wye-delta) combinations. Includes paralleling bridge, reversing bridge and star-delta bridge. Does not include mechanical interlock, see table on this page.

## Paralleling Bridge

|   | For Use with...   | Pkg. Qty. <sup>②</sup> | Catalog Number  |
|---|-------------------|------------------------|-----------------|
|  | XTCE007B–XTCE015B | 20                     | <b>XTCEXPBB</b> |
|  | XTCE018C–XTCE032C | 20                     | <b>XTCEXPBC</b> |

Component part of reversing link kit (XTCEXRL\_). Parallels the phases on the line-side of two contactors.

## Reversing Bridge

|   | For Use with...   | Pkg. Qty. <sup>②</sup> | Catalog Number  |
|---|-------------------|------------------------|-----------------|
|  | XTCE007B–XTCE015B | 20                     | <b>XTCEXRBB</b> |
|  | XTCE018C–XTCE032C | 20                     | <b>XTCEXRBC</b> |
|   | XTCE040D–XTCE065D | 10                     | <b>XTCEXRBD</b> |

Component part of reversing link kit (XTCEXRL\_). Reverses the phases on the load-side of two contactors.

## Notes

- ① For two contactors with AC or DC operated magnet system which are horizontally or vertically mounted. For Frames B–G, mechanical lifespan is  $2.5 \times 10^6$  operations and the distance between contactors is 0 mm. For Frames L–N, mechanical lifespan is  $5 \times 10^6$  operations and no auxiliary contact can be mounted between the mechanical interlock and the contactor—the distance between contactors is 15 mm.
- ② Orders must be placed in multiples of package quantity listed.
- ③ XTCEXMLG and XTCEXMLN consist of an interlock element and mounting plate.
- ④ Also includes interlocking bridge (XTCEXLB). The following control cables are integrated for electrical interlock: K1M: A1–K2M: 21; K1M: 21–K2M: A1; K1M: A2–K2M: A2.