

Eaton XTCR032C21TD

Catalog Number: XTCR032C21TD

Eaton XT IEC contactor, 32A, 24-27 Vdc, 2NO-2NO, 32A, Frame C, 45 mm, 3, 5/ 10, 10, 20, 25 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Reversing, XT IEC series, Screw terminals, Full voltage reversing contactor

General specifications



Product Name

Eaton XT IEC contactor

Catalog Number

XTCR032C21TD

UPC

782116885695

Product Length/Depth

4.75 in

Product Height

4.5 in

Product Width

7.5 in

Product Weight

2.45 lb

Warranty

1 year

Compliances

CE Marked

RoHS Compliant

Certifications

CSA Certified

EN 60947

UL Listed

IEC 60947

Catalog Notes

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Product specifications

Amperage Rating

32A

HP rating - max

3, 5/ 10, 10, 20, 25 hp (1/3PH @ 115,230/200,230,460,575 V)

Number Of Poles

Three-pole

Type

Full voltage reversing contactor

Frame size

45 mm

Terminals

Screw terminals

Coil

24 Vdc

Coil voltage

24-27 Vdc

Contact configuration

2 NO, 2 NO

Continuous ampere rating

32 A

Series

XT IEC

Operation

Reversing

Resources

Drawings

[XTCR_C 3D Inventor](#)

[XTCR_C 2D Drawing Xchange](#)

[XTCR_C 2D PDF](#)

[XTCR_C AutoCAD 2D Footprint](#)

[XTCR_C 3D Model Xchange](#)

[XTCR_C AutoCAD 2D Footprint \(mm\)](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCR032C21TD](#)

Eaton XTCR032C21TD

Catalog Number: XTCR032C21TD

Eaton XT IEC contactor, 32A, 24-27 Vdc, 2NO-2NO, 32A, Frame C, 45 mm, 3, 5/ 10, 10, 20, 25 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Reversing, XT IEC series, Screw terminals, Full voltage reversing contactor

General specifications



Product Name

Eaton XT IEC contactor

Catalog Number

XTCR032C21TD

UPC

782116885695

Product Length/Depth

4.75 in

Product Height

4.5 in

Product Width

7.5 in

Product Weight

2.45 lb

Warranty

1 year

Compliances

CE Marked

RoHS Compliant

Certifications

CSA Certified

EN 60947

UL Listed

IEC 60947

Catalog Notes

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Product specifications

Amperage Rating

32A

HP rating - max

3, 5/ 10, 10, 20, 25 hp (1/3PH @ 115,230/200,230,460,575 V)

Number Of Poles

Three-pole

Type

Full voltage reversing contactor

Frame size

45 mm

Terminals

Screw terminals

Coil

24 Vdc

Coil voltage

24-27 Vdc

Contact configuration

2 NO, 2 NO

Continuous ampere rating

32 A

Series

XT IEC

Operation

Reversing

Resources

Drawings

[XTCR_C 3D Inventor](#)

[XTCR_C 2D Drawing Xchange](#)

[XTCR_C 2D PDF](#)

[XTCR_C AutoCAD 2D Footprint](#)

[XTCR_C 3D Model Xchange](#)

[XTCR_C AutoCAD 2D Footprint \(mm\)](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCR032C21TD](#)